

The table is based on 600 N/clip including safety factor 1.5:

Coil width [mm]	500		570		600		670		700	
Panel width [mm]	430		500		530		600		630	
Wind load [kN/m <sup>2</sup> ]	No. of clips [pc.]	Clip centre [mm]	Haftanzahl [St.]	Haftabstand [mm]	Haftanzahl [St.]	Haftabstand [mm]	Haftanzahl [St.]	Haftabstand [mm]	Haftanzahl [St.]	Haftabstand [mm]
-0,3	0,5	500	0,5	500	0,5	500	0,5	500	0,5	500
-0,6	1,0	500	1,0	500	1,0	500	1,0	500	1,0	500
-0,9	1,5	500	1,5	500	1,5	500	1,5	500	1,5	500
-1,2	2,0	500	2,0	500	2,0	500	2,0	500	2,0	500
-1,5	2,5	500	2,5	500	2,5	500	2,5	500	2,5	500
-1,8	3,0	500	3,0	500	3,0	500	3,0	500	3,0	500
-2,1	3,5	500	3,5	500	3,5	500	3,5	460	3,5	440
-2,4	4,0	500	4,0	500	4,0	460	4,0	400	4,0	380
-2,7	4,5	500	4,5	440	4,5	400	4,5	360	4,5	340
-3,0	5,0	460	5,0	400	5,0	360	5,0	320		
-3,3	5,5	420	5,5	360	5,5	340	5,5	300		
-3,6	6,0	380	6,0	320	6,0	300	6,0	260		
-3,9	6,5	340	6,5	300	6,5	280				
-4,2	7,0	320	7,0	280	7,0	260				
-4,5	7,5	300	7,5	260	7,5	240				
-4,8	8,0	280	8,0	240	8,0	220				
-5,1	8,5	260	8,5	220	8,5	220				
-5,4	9,0	240	9,0	220	9,0	200				
-5,7	9,5	240	9,5	200	9,5	180				
-6,0	10,0	220	10,0	200	10,0	180				
-6,3	10,5	220	10,5	180	10,5	160				
-6,6	11,0	200	11,0	180	11,0	160				
-6,9	11,5	200	11,5	160	11,5	160				
-7,2	12,0	180	12,0	160	12,0	140				
-7,5	12,5	180	12,5	160	12,5	140				
-7,8	13,0	160	13,0	140	13,0	140				
-8,1	13,5	160	13,5	140	13,5	120				
-8,4	14,0	160	14,0	140	14,0	120				
-8,7	14,5	160	14,5	120	14,5	120				
-9,0	15,0	140	15,0	120	15,0	120				
-9,3	15,5	140	15,5	120	15,5	120				
-9,6	16,0	140	16,0	120						
-9,9	16,5	140	16,5	120						