Corokap

Eaves closing comb

The eaves closing comb is made of flexible PVC, which prevents comb's elements againts breaking under the pressure of tiles. It protects eaves area and underside roof space from birds, rodents, insects access as well as blown-in leaves and twigs.




Advantages

- protects eaves' area and thermal-insulation againts access of birds, rodents as well as blown-in leaves and twigs
- ✓ provides great air-circulation of the roof space
- ✓ resistant to weather conditions and UV-rays

Application

for protecting the eaves area and underside roof space



Characteristics

Material	PVC
Colour	black, light brown, brick red
Length	1000 mm
Height	55 mm
Vicat softening temperature	≥ 70°C
Tensile strength	≥ 26 MPa
Relative elongation at break,	≥ 5,5 %
Dimensional and shape stability at over a period of 3 h, change in dimensions	temp. ≤ 1,0 % no defects, no shape changes

Installation

- 1. Place eaves closing comb on the support batten, and then fix it.
- 2. Install the next batten on which the tiles are mounted so that the tile enters the gutter between 1/4 and 1/2 of its width.

The product has passed a positive assessment of its performance for the intended use: ventilation and roofing. Confirmation document: National Technical Assessment No. ITB-KOT-2020/1462 edition 1.

Storage

The product should be stored in dry and covered places, protected against deformations. Transport it by covered means of transport, adequately protecting against damage.

Packaging

Quantity per box (pcs.):	300
Quantity on a pallet (pcs):	4800

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.