

## STAINLESS SELF TAPPING FACADE SCREW, A

### SCREW FOR FASTENING OF STEEL CLADDING TO WOOD OR STEEL

- Tapping and fastening in one operation
- Stainless steel screw A2
- Supplied with Ø16 mm stainless washer vulcanized with EPDM for better load distribution and increased sealing abilities
- Also available without washer
- See chart of predrilling in different steel thicknesses



#### PRODUCT RANGE

MG:06 PG:4230 HWH A RX 6.5 X L "RX" HX8 RX-16G



Art.no.	Item name	Washer [mm]	Thread [mm]	Length L [mm]	Steel thickness [mm]	Head [mm]	Unit
10772	HWH A RX 6.5 X 19 "RX" HX8 RX-16G	A2 Ø16	Ø6.5	19	max. 3.0	HEX 8.0	250
10778	HWH A RX 6.5 X 25 "RX" HX8 RX-16G			25			
10779	HWH A RX 6.5 X 32 "RX" HX8 RX-16G			32			
10780	HWH A RX 6.5 X 38 "RX" HX8 RX-16G			38			
10781	HWH A RX 6.5 X 45 "RX" HX8 RX-16G			45			
10782	HWH A RX 6.5 X 50 "RX" HX8 RX-16G			50			100
10783	HWH A RX 6.5 X 55 "RX" HX8 RX-16G			55			
15486	HWH A RX 6.5 X 60 "RX" HX8 RX-16G			60			
10784	HWH A RX 6.5 X 65 "RX" HX8 RX-16G			65			
15487	HWH A RX 6.5 X 70 "RX" HX8 RX-16G			70			
15686	HWH A RX 6.5 X 75 "RX" HX8 RX-16G			75			

Steel thickness	Drill diameter
< 0.63	Ø4.0 mm
0.63 - 2.0 mm	Ø4.2 mm
2.0 - 3.0 mm	Ø5.0 mm

#### APPLICATION

