

ANETA







LIGHTING

LIGHTS FOR HOME AND WORK SINCE 1947

SENSILO

60914

Typ 60914-a



SENSILO

60914

Typ 60914-a

ANETA

LIGHTING

LIGHTS FOR HOME AND WORK SINCE 1947

NO: Dette produktet inneholder en lyskilde med energieffektivitetsklasse F. Diodelyskilden i armaturen er ikke utskiftbar, når lyskildens levetid er slutt skal hele armaturen byttes. 50000 tim ≈ 20 år (6 tim/dag)

SE: Denna produkt innehåller en ljuskälla med energieffektivitetsklass F. Lysdioden i armaturen är inte utbytbar, när ljuskällans livstid är slut ska hela armaturen bytas. 50000 tim ≈ 20 år (6 tim/dag)

FI: Tämä tuote sisältää valonlähteen, jonka energiatehokkuusluokka on F. Valaisimen valolähde ei ole vaihdettavissa. Kun valolähteen elinkaari on loppu niin koko valaisin on vaihdettava. 50 000 tuntia ≈ 20 vuotta (6 t/päivä)

EN: This product contains a light source of energy efficiency class F. The diode lamp of vthis luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced. 50000 h ≈ 20 years (6 h/day)

Light Source :

Lighting technology used:	LED	CCT colour temperature:.....	3000 K
Mains or non-mains:	non-mains	On-mode power:	4,0 W
Directional or non-directional:	non-directional	Stand-by power:	0 W
Connected L.S.:	no	Networked standby power:	0 W
Color-tuneable:	no	CRI:	≥ 80
Envelope:	no	R9 color rendering index:	0
High luminance:	no	Chromaticity coordinates:	x:0.442, y:0.404
Anti-glare shield:	no	SDCM:	< 6
Dimmable:	yes	Lifetime L ₇₀ B ₅₀ :	50 000 hours
Energy consumption in on-mode: ..	4 kWh / 1000 h	Lumen maintenance factor:	0,96
Energy efficiency class (A-G):	F	Survival factor:	0,90
Useful luminous flux:.....	400 lm	Measures LxBxH:	mm
CCT colour temperature:.....	3000 K	Supply current:	12VDC

* The luminous flux stated here is the value for the light source itself in accordance with Regulation (EU) 2019/2015. On the box the luminous flux for the lighting fitting is stated, where the light is partly absorbed by glass/glare shield/shade and parts of the fitting, why it is lower than for the light source.

SE: Kabeln kan ej bytas ut. Om kabeln på lampan blir skadad skall lampan förstöras och lämnas till återvinningsstation.
Rengöring: Torkas med torr trasa.

NO: Ledningen kan ikke skiftes. Hvis ledningen til lampen blir skadet må lampen ødelegges og leveres til gjenvin.
Rengjøring, Tørkes av med tørr klut.

FI: Johtoa ei voi vaihtaa. Jos johto on vahingoittunut tuhoa valaisin ja toimita valaisin kierrätyspisteeseen.
Puhdistus: Pyyhi kuivalla liinalla.

EN: The cable or cord of this luminaire cannot be replaced. If the cord is damaged the luminaire shall be destroyed and left to recycling.
Cleaning: Wipe with a dry cloth.