

Product No: CBLUSB00

RED LION CABLE - CONNECTS USB TYPE A -B CBLUSB00

FEATURES

- PID Controller with multiple DIN sizes: 1/4, 1/8, 1/16
- Power Connection options: AC 100 to 240 VAC or DC 24 VDC
- Supports Thermocouple Types T, E, J, K, R, S, B, N, L, U, TXK
- Accepts RTD Inputs Type 2 or 3 wire with Excitation of 180 mA
- Process Inputs include: 0-5 or 0-10 VDC; 0-20 or 4-20 mA; and 0-50 mV
- Optional CT Input for current measurement: 0 to 25 mA AC (Single phase)
- Remote Input compatibility: 0-10 VDC; 0-20 mA; and 4-20 mA
- Communication via RS-485 serial interface



General Information

Brand	RED LION
Product Type	Accessory
Series	PXU
Suitable For	Graphite Series, G3 Series

Technical Attributes

Nominal Power (W)	5
Rated Minimum Operational Voltage DC (V)	24

Physical Attributes

Maximum Temperature (°C)	50
Minimum Temperature (°C)	0

Dimensions

Cable Length (m)	3.05
------------------	------

Protection & Standards

Degree of Protection

IP65

Resources

Product catalogue (Flipbook)

[Download from here](#)
