

Product No: 943 940-999-002

HIRSCHMANN MANAGED RACKMOUNT SWITCH MAR1020-99

TTTTTTTTTBBBBBB9999999999SMMHPH 943 940-999-002

FEATURES

- Ruggedized Managed Rackmount Switch
- 2 Combo Ports (2 x 10/100/1000 TX or 2 x GE SFP)
- 20 Twisted Pair (TX) 10/100 Mbit/s RJ45 ports
- Operating temperature range from 0 °C to +60 °C
- Dual power supply: 110/250 V DC, 110/230 V AC (plug-in connector)
- Layer 2 Professional networking features
- Approvals include cUL508, cUL1604 Class 1 Div2, Germanischer Lloyd, IEC 61850-3, IEEE 1613, EN 50121
- Designed for mounting in a standard 19" control cabinet
- Equipped with two fiber ports and twenty Ethernet ports

General Information

Brand	HIRSCHMANN
Series	MAR1030

Technical Attributes

No. of 100Mb Ports	14
No. of Ethernet Ports	8
No. of Fiber Ports	6
Rated Maximum Operational Voltage AC (V)	230
Rated Maximum Operational Voltage DC (V)	250
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110

Physical Attributes

Maximum Temperature (°C)	60
Minimum Temperature (°C)	0
Mounting Type	19" Control Cabinet

Protection & Standards

Degree of Protection	IP30
Standards and Approvals	IEC 61850-3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------