

Product No: 471400013100M00112000

BD SENSORS LMK351 SCREW-IN TRA NSMITTER LMK351 SCREW-IN TRANSMITTER 471400013100M00112000

FEATURES

- Pressure port PVDF-version for aggressive media.
- Pressure port G 11/2" for pasty and polluted media.

General Information	
Brand	BDSENSORS
ProductSeries	LMK 351
ProductType	Ceramic Sensor
Suitable For	Fuel and oil. Viscous and pasty media.
Version	Standard

Technical Attributes	
Accuracy	0.35 % FSO
Application	Plant and machine engineering. Environmental engineering (water – sewage – recycling).
Electrical Connection	Male and female plug ISO 4400
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Mechanical Connection	G11/2" DIN 3852 with flush sensor.
Mechanical Stability	Vibration: 10 g RMS (20 2000 Hz) according to DIN EN 60068-2-6. Shock: 100 g / 1 msec according to DIN EN 60068- 2-27.
Operational Life	100 million load cycles.
Output Signal	4 20 mA / 2-wire
Permissible Temperatures	Medium: -40 125 °C Electronics / Environment: -40 85 °C Storage: -40 100 °C



Pressure Port	Stainless steel 1.4404 (316L)
Response Time (ms)	Mean response time: ≤ 200 Max. response time: 380
Seals	FKM

Physical Attributes

Diaphragm Material

Ceramics Al2O3 96 %

Resources

Product catalogue (Flipbook)

Download from here