


Product No: MC2A310ATN

ABB MINI CONTACTOR 3P (3NO), 5.5kW 400V AC CONTROL 220-240V AC, AUX 1NO MC2A310ATN

FEATURES

- Compact Design, suitable for applications with limited space
- Capable of efficiently controlling loads up to 5.5kW, ensuring reliable operation
- Ideal for both residential and industrial settings
- Suitable for wall or rail mounting



General Information

Brand	ABB
Product Type	Mini Contactor
Series	M

Technical Attributes

Auxiliary Contacts	1NO
Mode of Operation	AC
No. of Normally-open Contacts	3
No. of Poles	3
Power Loss (W)	0.7/Pole AC-1
Rated Control Circuit Voltage AC (V)	220 - 240
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	750
Rated Operational Current AC-1 400V (A)	20
Rated Operational Power AC-3 400V (kW)	5.5
Rated Operational Voltage AC (V)	690
Terminal Type	Screw

Physical Attributes

Mounting Type	DIN Rail/Wall
---------------	---------------

Operational Temperature Range (°C) -40 to +55

Dimensions

Dimensions (mm) 45W x 48H x 56D

Protection & Standards

Degree of Protection IP20

Resources

Product catalogue (Flipbook) [Download from here](#)
