

## ABB DS201MC40F30 RCBO 10kA 1P+N 40A C CURVE TYPE F 30mA

DS201MC40F30

### FEATURES

- Protection against short circuit, thermal overload and earth leakage
- Contact Position Indication (CPI)
- Earth fault indicator to identify easier earth faults
- Test pushbutton to verify the correct functioning of the device
- Laser printed data for quick identification
- Finger safety with IP20 terminals
- Pole configuration 1P+N



### GENERAL INFORMATION

Brand	ABB
Product Type	RCBO
Series	DS201MC

### TECHNICAL ATTRIBUTES

Application	Commercial and Industrial
Breaking Capacity 230V AC - Icu (kA)	15
Curve Type	C Curve
No. of Poles	1P+N
Power Loss (W)	5.0
Rated Conditional Short-Circuit Current - Inc (kA)	15
Rated Current (A)	40
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230/240
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	10
Rated Voltage AC (V)	230
Test Voltage (kV)	0.17-0.264
Type of Residual Current	F

**PHYSICAL ATTRIBUTES**

Housing Material	Insulation Group I - II, RAL 7035
Mounting Type	DIN Rail

**PROTECTION & STANDARDS**

Degree of Protection	IP40 (Housing), IP20 (Terminals)
Pollution Degree	2

**RESOURCES**

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------