

Product No: 1SDA070881R1

ABB E1.2N 1600 EKIP DIP LI 3P F F 1SDA070881R1

FEATURES

- IP30 protection for fixed parts
- Adjustable rear terminals
- Racked-out mechanism lock, anti-insertion lock, standard shutter lock
- Lever for racking in/out
- AUX 4Q 400V Open-Closed changeover contact
- TU Reset push button
- S51 250V trip indicator



General Information

Brand	ABB
Product Type	Automatic ACB
Version	Fixed

Technical Attributes

Design of Control Element	Push Button
Breaking Capacity 400V AC - Icu (kA)	66
Current Type	AC
Indication	Switched-off Indicator
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Back Side
No. of Auxiliary Change-over Contacts	4
No. of Poles	3
Overload Release Current Setting (A)	640
Power Loss (W)	201
Rated Current (A)	1600
Rated Impulse Withstand Voltage (kV)	12
Rated Instantaneous Short-Circuit Current - Ii (A)	2400
Rated Insulation Voltage AC (V)	1000
Rated Short-time Withstand Current - Icw (kA/1s)	50
Rated Short-time Withstand Current - Icw (kA/3s)	30
Rated Uninterrupted Current - Iu (A)	1600
Rated Voltage (V)	690

Technical Attributes

Terminal Type	Front
Trip Unit	EKIP DIP LI

Dimensions

Dimensions (mm)	270W x 350H x 330D
Size of Frame	E1.2

Protection & Standards

Degree of Protection	IP30
----------------------	------