

## Product No: 261798

### STAHL 9494/S1-B2 REMOTE I/O IS1+ BUSRAIL FOR 2 MODULES, BEGINNING 261798

#### FEATURES

- Binary output Ex i field circuit
- Single channel configuration
- Auxiliary power: 24 V DC (operating range 19.2 to 30 V)
- Nominal auxiliary supply current: 90 mA
- Input voltage for ON state: 15.0 30.0 V
- Input voltage for OFF state: 0.0 5.0 V
- Output voltage: 24.3 V
- Output current: 48 mA
- Slim design with a width of only 12.5 mm



#### General Information

|              |         |
|--------------|---------|
| Brand        | STAHL   |
| Product Type | BusRail |
| Series       | 9494    |

#### Technical Attributes

|              |               |
|--------------|---------------|
| No. of Slots | For 2 Modules |
|--------------|---------------|

#### Physical Attributes

|                                |            |
|--------------------------------|------------|
| Ambient Temperature Range (°C) | -40 to +75 |
| Maximum Temperature (°C)       | 75         |
| Minimum Temperature (°C)       | -40        |
| Mounting Type                  | DIN Rail   |

#### Dimensions

|                 |                  |
|-----------------|------------------|
| Dimensions (mm) | 197W x 15H x 35D |
|-----------------|------------------|

#### Protection & Standards

|                      |             |
|----------------------|-------------|
| Certifications       | IECEx, ATEX |
| Degree of Protection | IP30        |

Standards and Approvals

ATEX/IECEx

---

## Resources

Product catalogue (Flipbook)

[Download from here](#)

---