

## Product No: ISDA100417R1

### ABB XT5S 630 TMA 630-6300 3P F F ISDA100417R1

#### FEATURES

- Fixed Three Pole
- Front Terminals
- Thermo-magnetic release
- ABB EcoSolutions



#### General Information

Brand	ABB
Product Type	MCCB
Version	Fixed

#### Technical Attributes

Design of Control Element	Toggle
Breaking Capacity 415V AC - Icu (kA)	50
I - Short-circuit Current Setting I3 (A)	3150 - 6300
L - Overload Current Setting II (A)	441 - 630
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Front Side
No. of Poles	3
Overload Release Current Setting (A)	252
Power Loss (W)	47.8
Rated Current (A)	630
Rated Frequency (Hz)	50/60
Rated Instantaneous Short-Circuit Current - Ii (A)	3150
Rated Insulation Voltage (V)	1000
Rated Uninterrupted Current - Iu (A)	630
Rated Voltage (V)	690
Trip Unit	TMA

#### Dimensions

Dimensions (mm)	140W x 205H x 103.5D
-----------------	----------------------

## Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 60947-2