

## Product No: EMX4i0735CV5C2H

## AuCom EMX4i0735CV5C2H SOFT STARTER 735A 200-525VAC W/O EXT. BYPASS, CONTROL 24VAC/DC

## **FEATURES**

- - Dual motor parameter settings
- - Constant current and current ramp start
- XLR-8 adaptive control starting/stopping
- - Coast to stop and timed voltage ramp stop
- - Soft trip
- - Configurable multi-language graphical display
- - Quick start application setup for easy commissioning.
- - Emergency run mode
- Simulation testing (Run, Protection and Signaling)
- - USB port for easy and fast configuration backups and data protection.
- - Real time metering and monitoring
- - Automated pump clean function
- - SCR fail power through operation
- Scheduled automatic start/stop (Time of day & day of week)
- - Motor voltage and power measurement
- - Automation functions with optional smart card
- Up to 1620A with External Bypass (Non internal bypass starter)
- - Voltage Ranges: 200 ~ 525 VAC (V5)
- - Protection: IP20/IP00



General Information	
Brand	AuCom
Product Type	Advanced Smart - EMX4i

Technical Attributes	
Rated Control Supply Voltage AC/DC (V)	24
Rated Current - Heavy Duty (A)	492
Rated Current - Light Duty (A)	735
Rated Current - Medium Duty (A)	590
Rated Current - Severe Duty (A)	404
Rated Supply Voltage AC (V)	200 - 525



Physical Attributes		
Operational Temperature Range (°C)	-10 to +60	
Dimensions		
Dimensions (mm)	446W x 618H x 310D	
Size of Frame	\$3	
Protection & Standards		
Degree of Protection	IPO O	
Resources		
Product catalogue (Flipbook)	Download from here	