

Product No: 3AXD50001063115

ABB ACS580 45KW 89A IP55 GENERAL PURPOSE DRIVE W/ CP ACS580-01-089A-4+B056+J400 3AXD50001063115

FEATURES

- ACS580-01 is plug-in ready for controlling compressors, conveyors, pumps, extruders, centrifuges, mixers, fans, and more.
- Suitable for variable and constant torque applications across various light industries (e.g., food & beverage, plastic, textile, material handling, agriculture).
- All essential features are built-in, eliminating the need for additional hardware.
- Versatile and straightforward settings menu with assistants for fast setup, commissioning, use, and maintenance.
- Rugged and robust design, ideal for different environments.
- Provides full control of processes for comprehensive plant management.
- ACS580-01 comes in an IP21 wall-mounted enclosure as standard.
- IP55 and flange mounting options are available.



General Information

Efficiency Level	IE2
Country of Origin	Finland (FI)

Technical Attributes

Communication Protocols	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Input Voltage (V)	380 ... 480
No. of Analogue Inputs	2
No. of Analogue Outputs	2

No. of Digital Outputs	3
No. of Phases	3
Output Current (A)	89
Power Factor	0.98
Rated Frequency (Hz)	47.5 ... 63

Physical Attributes

Mounting Type	Wall-mounted
Net Weight (g)	25

Dimensions

Height (mm)	636
Length (mm)	203
Width (mm)	265

Protection & Standards

Degree of Protection	IP55
----------------------	------