

Product No: NSPI-40-320-N

**NOVARIS TYPE 2 SPD, 40KA, FOR LV POWER SYSTEM PROT.
NSPI-40-320-N**



General Information

Brand	NOVARIS
Product Type	Surge Protection Device
Series	NSP

Technical Attributes

Connection Type	Shunt
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	4 (L-N)
Maximum Continuous Operating Voltage MCOV AC (V)	320 (L-N), 255 (N-PE)
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	40 (L-N, N-PE)
No. of Phases	1
No. of Poles	1P+N+PE
Nominal Discharge Current (8/20 μ s) - I _n (kA)	20 (L-N, N-PE)
Nominal Voltage AC (V)	230
Voltage Protection Level - U _p (kV)	<1.5 (L-N)

Physical Attributes

Mounting Type	DIN Rail
Operational Temperature Range (°C)	-40 to 70

Dimensions

Dimensions (mm)	36W x 65H x 98L
Weight (kg)	0.2

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 61643-11

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------



TECHNICAL DRAWING

