

Product No: SLH2-36-G

NOVARIS HIGH ENERGY SIGNAL LINE SURGE PROTECTOR 1 PAIR 20kA SLH2-36-G

FEATURES

- - Plug-in signal line protector
- - Multistage protection
- - For most twisted pair signalling schemes
- - Visual indicator & Alarm contacts
- - Replaceable cartridge



General Information

Brand	NOVARIS
Product Type	Signal Line Protector
Series	SLH2

Technical Attributes

Connection Type	Series
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	2.5 kA per line (5 kA common mode)
Maximum Continuous Operating Voltage MCOV AC (V)	30
Maximum Continuous Operating Voltage MCOV DC (V)	36
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	10 (per line), 20 common mode)
Maximum Load Current - I _n (A)	2.5
No. of Pairs	1
Voltage Protection Level (1kV/ μ s) - Up (kV)	0.07 (L-L), 0.4 (L-PE)

Physical Attributes

Mounting Type	DIN rail
Operational Temperature Range (°C)	-40 to 70

Dimensions

Dimensions (mm)	110H x 12W x 71D
-----------------	------------------

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 61643-21, AS/NZS 1768, UL497, A, B, AS/NZS 4117

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------