

ABB F202A40AP-R RCCB 10kA 1P+N 40A TYPE AP-R 30mA INDUSTRIAL

F202A40AP-R

FEATURES

- Protection for people and buildings against earth leakage faults
- Used where earth fault waveform may be sinusoidal or pulsating DC
- Test button for checking the correct function of the device
- Bidirectional cylindrical clamps assist and increase safety during connecting procedures
- Contact Position Indication (CPI)
- Laser printed data for quick identification
- Pole configuration 1P+N



GENERAL INFORMATION

Brand	ABB
Product Type	RCCB
Series	F200

TECHNICAL ATTRIBUTES

Application	Commercial and Industrial
No. of Poles	2P
Power Loss (W)	2.4/pole
Rated Conditional Short-Circuit Current - Inc (kA)	10
Rated Current (A)	40
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	10
Rated Voltage AC (V)	230/400
Type of Residual Current	AP-R

PHYSICAL ATTRIBUTES

Mounting Type	DIN Rail
---------------	----------



PROTECTION & STANDARDS

Degree of Protection IP20

Pollution Degree 2

RESOURCES

Product catalogue (Flipbook) [Download from here](#)