

## Product No: 4713000E3100M00112000

BD SENSORS LMK351 SCREW-IN TRA NSMITTER LMK351 SCREW-IN TRANSMITTER 4713000E3100M00112000

## FEATURES

- Pressure port PVDF-version for aggressive media.
- Pressure port G 11/2" for pasty and polluted media.



General Information	
Brand	BD SENSORS
ProductSeries	LMK 351
ProductType	Ceramic Sensor
Suitable For	Fuel and oil. Viscous and pasty media.
Version	Standard

Technical Attributes	
Accuracy	0.35 % FSO
Application	Plant and machine engineering. Environmental engineering (water – sewage – recycling).
Electrical Connection	Male and female plug ISO 4400
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Input Pressure (bar)	0.3
Mechanical Connection	G11/2" DIN 3852 with flush sensor.
Mechanical Stability	Vibration: 10 g RMS (20 2000 Hz) according to DIN EN 60068-2-6. Shock: 100 g / 1 msec according to DIN EN 60068- 2-27.
Operational Life	100 million load cycles.
Output Signal	Intrinsic safety 4 20 mA / 2-wire



Electronics / Environment: -40 ... 85 °C Storage: -40 ... 100 °C

Pressure Port

Seals

Response Time (ms)

Stainless steel 1.4404 (316L) Mean response time: ≤ 200

Max. response time: 380

FKM

## Physical Attributes

Diaphragm Material

Ceramics Al2O3 96 %

## Resources

Product catalogue (Flipbook)

Download from here