

Product No: 101157371

SCHMERSAL SAFETY SWITCH 1 AUXILIARY CONTACT 101157371

Note: Individual coding available on request



General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	Low
EAN	4030660000000
eCl@ss Number, Version 11.0	27-44-01-02
eCl@ss Number, Version 9.0	27-37-14-03
ETIM 6.0	EC000030
ETIM 7.0	EC011141
Housing Construction Form	Norm construction design
Product Type	Safety Switch
Working Principle	Electromechanical

Technical Attributes

No. of Auxiliary Contacts	2
Contact Material	Silver
Maximum Actuating Speed (m/s)	1
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	6 A gG D-fuse
Minimum Cable Cross Section (mm ²)	0.34
Minimum Mechanical Life	10000000 Operations
Minimum Positive Break Force (N)	20
No. of Safety Contacts	1

Overvoltage Category	3
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	250
Rated Short-circuit Current (A)	1000
Switching Element	NO contact, NC contact
Switching Principle	Slow action
Terminal Type	Screw terminals M20 x 1.5
Thermal Test Current (A)	0.25
Utilisation Category	DC-13 AC-15
Utilisation Category DC-13	0.05 A

Physical Attributes

Enclosure Material	Aluminium
Gross Weight (g)	240
Maximum Ambient Temperature (°C)	70
Minimum Ambient Temperature (°C)	-30
Net Weight (g)	230
Storage Temperature (°C)	25 to 85
Wire Cross-Section	13 AWG

Dimensions

Sensor Height (mm)	25
Sensor Length (mm)	33

Protection & Standards

Degree of Protection	IP40
Standards	EN IEC 61496-1 / EN IEC 61496-2

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------