

Product No: OT400E03CP

ABB OT 400E03CP CHANGE-OVER SWITCH OT 400E03CP

FEATURES

- High current capacity, making it suitable for applications with high electrical demands
- Robust and secure handle design featuring padlockable positions for added safety
- Mechanism at the end of the switch
- Convenient front operation



General Information	
Brand	ABB
Included	Handle, Shaft
Product Type	Manual
Suitable For	Distribution Board Installation
Туре	Main Switch

Conventional Free-Air Thermal Current - Ith (A) Indication I-O-II Maximum Operational Voltage AC (V) Mode of Operation Front No. of Poles No. of Switches 1 Padlockable Padlockable Position of Line Terminals Power Loss (W) Rated Impulse Withstand Voltage (kV) Rated Operational Current AC-21A 415V (A) 400	
Maximum Operational Voltage AC (V) Mode of Operation Front No. of Poles No. of Switches 1 Padlockable Position of Line Terminals Power Loss (W) Rated Impulse Withstand Voltage (kV) Rated Insulation Voltage (V) 1000	
Mode of OperationFrontNo. of Poles3No. of Switches1PadlockablePadlockable in OPosition of Line TerminalsTop In - Bottom OPower Loss (W)10Rated Impulse Withstand Voltage (kV)12Rated Insulation Voltage (V)1000	
No. of Poles 3 No. of Switches 1 Padlockable Padlockable in O Position of Line Terminals Top In - Bottom O Power Loss (W) 10 Rated Impulse Withstand Voltage (kV) 12 Rated Insulation Voltage (V) 1000	
No. of Switches 1 Padlockable Padlockable in O Position of Line Terminals Top In - Bottom O Power Loss (W) Rated Impulse Withstand Voltage (kV) Rated Insulation Voltage (V) 10 100	
Padlockable Position of Line Terminals Top In - Bottom C Power Loss (W) Rated Impulse Withstand Voltage (kV) Rated Insulation Voltage (V) 1000	
Position of Line Terminals Top In - Bottom C Power Loss (W) Rated Impulse Withstand Voltage (kV) Rated Insulation Voltage (V) 1000	
Power Loss (W) 10 Rated Impulse Withstand Voltage (kV) 12 Rated Insulation Voltage (V) 1000	-position
Rated Impulse Withstand Voltage (kV) 12 Rated Insulation Voltage (V) 1000	Out, Bottom In - Top Out
Rated Insulation Voltage (V) 1000	
Rated Operational Current AC-21A 415V (A) 400	
Rated Operational Current AC-22A 415V (A) 400	
Rated Operational Current AC-23A 380-415V (A) 400	



Physical Attributes	
Control Element Colour	Black
Handle Type	Pistol
Interlockable	Yes
Mounting Type	Front Mount 4-hole

Dimensions	
Dimensions (mm)	221W x 185H x 203D
Weight (kg)	5.9

Protection & Standards	
Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3

Resources	
Product catalogue (Flipbook)	Download from here