


Product No: RFIV-5AIBL-D24

IDEC RELAY, 6 POLE, 5NO, 1NC, 6A, 24V DC, FORCE GUIDED FOR SAFETY CIRCUITS RFIV-5AIBL-D24

FEATURES

- With LED Indicator
- Force guided contact mechanism
- (EN50205 Type A TÜV approved)
- Finger-safe DIN rail mount socket and PC board mount socket



General Information

Brand	IDEC
Product Type	Force Guided

Technical Attributes

Coil Voltage DC (V)	24
Contact Resistance (mΩ)	100
Insulation Resistance (MΩ)	1000
Maximum Switching Capacity AC (V)	250
Maximum Switching Capacity AC (VA)	1500
Maximum Switching Capacity DC (V)	30
Maximum Switching Capacity DC (W)	180
Maximum Switching Current (A)	6
Minimum Mechanical Life	10,000,000
No. of Normally-closed Contacts	1
No. of Normally-open Contacts	5
No. of Poles	6
Power Consumption (W)	0.5
Rated Current (mA)	20.8
Resistance to Shock (m/s ²)	200
Resistance to Vibrations	10 to 55Hz

Physical Attributes

Operating Humidity	5 to 85%
Operational Temperature Range (°C)	-40 to 85

Dimensions

Dimensions (mm)	50W x 24H x 13D
Weight (g)	23

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------