

## Product No: DGM TT150FM

### DEHN SPD 4P CLASS 2 40KA 8/20US4C+EA 150VAC NON-MEN C/W CO DGM TT150FM

#### FEATURES

- Multipole DEHNguard M surge arrester
- Consisting of a base part and plug-in protection modules
- High reliability due to "Thermo Dynamic Control" SPD monitoring device
- For protecting low-voltage consumer's installations against surges
- For installation in conformity with the lightning protection zone concept at the boundaries from OB "1 and higher



#### General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	952328
Suitable For	Power Supply Systems

#### Technical Attributes

Breaking Capacity AC (kA)	50
Lightning Impulse Current (10/350 $\mu$ s) - Iimp (kA)	12
Maximum Continuous Voltage AC (V)	150
Maximum Discharge Current (8/20 $\mu$ s) - I <sub>max</sub> (kA)	40
No. of Conductors	4
Nominal Discharge Current (8/20 $\mu$ s) - I <sub>n</sub> (kA)	15
Nominal Voltage AC (V)	120/240

#### Dimensions

Dimensions (mm)	72W x 90H x 66D
Weight (kg)	0.39

### Protection & Standards

Degree of Protection	IP20
Standards and Approvals	EN 61643-11

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------