

## Product No: ISDA068231R1

### ABB XT3S 250 TMD 200-2000 4P F F INN=100% ISDA068231R1

#### FEATURES

- Fixed Four Pole
- Front Terminals
- Thermo-magnetic release
- ABB EcoSolutions



#### General Information

Brand	ABB
Product Type	MCCB
Version	Fixed

#### Technical Attributes

Design of Control Element	Toggle
Breaking Capacity 415V AC - Icu (kA)	50
I - Short-circuit Current Setting I3 (A)	2000
L - Overload Current Setting II (A)	140 - 200
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Front Side
No. of Poles	4
Overload Release Current Setting (A)	140
Power Loss (W)	13.2
Rated Current (A)	200
Rated Frequency (Hz)	50/60
Rated Instantaneous Short-Circuit Current - Ii (A)	2000
Rated Insulation Voltage (V)	800
Rated Uninterrupted Current - Iu (A)	250
Rated Voltage (V)	690
Trip Unit	TMD

#### Dimensions

Dimensions (mm)	140W x 150H x 70D
-----------------	-------------------

## Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 60947-2