

Product No: PSE210-600-70-1

ABB PSE210-600-70-1 SOFT STARTER - 210 A - 208 ... 600 V AC PSE210-600-70-1

FEATURES

- Offers two-phase control with a smooth start and stop using voltage or torque ramps
- Built-in bypass for energy saving and easy installation
- Ensures reliable and secure motor performance with features such as kickstart, EOL and locked rotor protection
- User-friendly illuminated display with language-neutral symbols



General Information

Brand	ABB
Product Type	General - PSE

Technical Attributes

Actuating Voltage Type	AC
Display Screen	Yes
Function	Torque Control
IEC Rated Operational Power 400V - Heavy (kW)	90
IEC Rated Operational Power 400V - Normal (kW)	110
Overload Protection	Yes
Rated Control Supply Voltage AC (V)	100
Rated Current - Heavy Duty (A)	171
Rated Current - Medium Duty (A)	210
Rated Operational Current (A)	210
Rated Operational Power - In-Line Connection (230V) (kW)	59
Rated Operational Power - In-Line Connection (400V) (kW)	110
Rated Operational Voltage AC (V)	208
Rated Supply Voltage AC (V)	100
Release Class	Adjustable

Physical Attributes

Operational Temperature Range (°C)	-25 to +60
------------------------------------	------------

Dimensions

Dimensions (mm)	190W x 435H x 237D
-----------------	--------------------

Size of Frame	C
---------------	---

Protection & Standards

Degree of Protection	IP00
----------------------	------

NEMA Degree of Protection	1
---------------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------