

Product No: 68581940

ABB ACS150 0.37KW 2.4A IP20 1P MICRO DRIVE ACS150-01E-02A4-2

FEATURES

- - Power range 0.37 to 4 kW/0.5 to 5 Hp
- - IP20 enclosure
- - Scalar control
- - Integrated user interface and potentiometer
- - Built-in brake chopper, EMC filter for second environment
- - Coated boards
- - Pre-defined connection macros



General Information

Brand	ABB
Product Type	Micro
Reference No.	ACS150-01E-02A4-2
Series	ACS150

Technical Attributes

No. of Analogue Inputs	1
No. of Digital Inputs	5
No. of Phases	1
No. of Relay Outputs	1
Output Current - Light Duty (A)	2.4
Output Current - Normal Duty (A)	2.4
Output Power - Light Duty (kW)	0.4
Output Power - Normal Duty (kW)	0.37
Rated Supply Voltage AC (V)	200 - 240

Physical Attributes

Ambient Temperature Range (°C)	-10 to 40 (No frost allowed)
Mounting Type	Cabinet

Dimensions

Dimensions (mm)	239H x 70W x 142D
-----------------	-------------------

Size of Frame	R0
---------------	----

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	UL, cUL, CE, RCM, RoHS and EAC
-------------------------	--------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------