

## **Product No: B7400001**

## ABB B7-40-00-01 MINI CONTACTOR 24 V AC - 4 NO - 0 NC - SCREW TERMINALS B7400001

## **FEATURES**

- Space saving contactor with screw terminals
- Ensures high reliability, making it suitable for residential, commercial and industrial use
- Controls single or three phase loads, ideal for diverse applications
- Noiseless and hum-free coil for quiet operation
- Integrated features for easy rail or wall mounting, providing flexibility in installation



General Information	
Brand	ABB
Product Type	Mini Contactor

Technical Attributes	
Actuating Voltage Type	AC
Auxiliary Contacts	4NO
Main Circuit Electrical Connection	Screw Connection
No. of Normally-open Contacts	4
No. of Poles	4
Operating Voltage AC (V)	220
Power Loss (W)	2.0/pole 1.4/pole AC-1
Rated Control Circuit Voltage AC (V)	24
Rated Control Supply Voltage AC (V)	24
Rated Control Supply Voltage DC (V)	24
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-1 240V (A)	20
Rated Operational Current AC-1 690V (A)	6
Rated Operational Power AC-3 400V (kW)	5.5
Rated Operational Power AC-3 415V (kW)	5.5
Rated Operational Voltage AC (V)	220



Technical Attributes	
Rated Supply Voltage AC (V)	24
Terminal Type	Screw

Physical Attributes	
Mounting Type	DIN Rail / Wall
Operational Temperature Range (°C)	-25 to +55

Dimensions	
Dimensions (mm)	52.5W x 57.5H x 46.7D

Protection & Standards	
Degree of Protection	IP20
Pollution Degree	3

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>