

Product No: 942 170-008

HIRSHMANN COMPACT MANAGED INDUSTRIAL SWITCH 8X GIG TX, 12-24V DC, 0-60°C, HIOS L2S 942170008

FEATURES

- Store and Forward Switching Mode
- Fanless design
- Ethernet/Fast-Ethernet Switch



General Information

Brand	HIRSHMANN
Product Type	Managed
Series	BRS40

Technical Attributes

Electromagnetic Capability	10 V/m (80-2000 MHz) 5 V/m (2000-2700 MHz) 3 V/m (5100-6000 MHz)
Electrostatic Discharge (kV)	6 kV Contact Discharge, 8 kV Air Discharge
No. of 1GB Ports	8
No. of Ethernet Ports	8
No. of Ports	8 x 10/100/1000BASE-TX RJ45
Nominal Power (W)	8
Power Consumption (W)	8
Rated Maximum Operational Voltage DC (V)	24
Rated Minimum Operational Voltage DC (V)	12
Rated Operational Voltage DC (V)	2 x 12 - 24
Resistance to Vibrations	5 Hz ... 8,4 Hz with 3,5 mm amplitude 2 Hz ... 13,2 Hz with 1 mm amplitude 8,4 Hz ... 200 Hz with 1 g 13,2 Hz ... 100 Hz with 0,7 g
Surge Voltage (kV)	Power Line: 2 kV (Line/Earth) and 1 kV (Line/Line); Data Line: 2 kV
Switch Type	Switch - Managed

Transition Type	2 kV Power Line, 2 kV Data Line
-----------------	---------------------------------

Physical Attributes

Maximum Temperature (°C)	60
Minimum Temperature (°C)	0
Mounting Type	DIN Rail
Operational Temperature Range (°C)	0 to +60
Relative Humidity	1- 95 %

Dimensions

Cable Length (m)	0 - 100
Dimensions (mm)	138H x 73W x 115D

Protection & Standards

Degree of Protection	IP30
Standards and Approvals	CE, FCC, EN61131, EN62368-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------