

ABB F204A25AP-R RCCB 10kA 3P+N 25A TYPE AP-R 30mA INDUSTRIAL

F204A25AP-R

FEATURES

- Protection for people and buildings against earth leakage faults
- Used where earth fault waveform may be sinusoidal or pulsating DC
- Test button for checking the correct function of the device
- Bidirectional cylindrical clamps assist and increase safety during connecting procedures
- Contact Position Indication (CPI)
- Laser printed data for quick identification
- Pole configuration 3P+N



GENERAL INFORMATION	
Brand	ABB
Product Type	RCCB
Series	F200

TECHNICAL ATTRIBUTES	
Application	Commercial and Industrial
No. of Poles	4P
Power Loss (W)	1.3/pole
Rated Conditional Short-Circuit Current - Inc (kA)	10
Rated Current (A)	25
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230/400
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	10
Rated Voltage AC (V)	240/415
Type of Residual Current	AP-R

PHYSICAL ATTRIBUTES	
Mounting Type	DIN Rail



PROTECTION & STANDARDS	
Degree of Protection	IP20
Pollution Degree	2
RESOURCES	
Product catalogue (Flipbook)	Download from here