

## IDEC PLUG-IN TIMER 8 PIN 12VDC SPDT GT3A-2D12

GT3A-2D12

### FEATURES

- 4 selectable operation modes on each model
- External start, reset, and gate inputs
- Panel mount or socket mount
- Large variety of timing functions
- Power and output status indicating LEDs



### GENERAL INFORMATION

Brand	IDEC
Product Type	Plug-In Timer
Series	GT3A

### TECHNICAL ATTRIBUTES

Contacts	Delayed SPDT + Instantaneous SPDT
Input Voltage AC (V)	100 - 240
Input Voltage AC/DC (V)	24
Input Voltage DC (V)	12
Insulation Resistance (Mega Ohm)	100
No. of Pins	8
Output Voltage AC (V)	24
Output Voltage DC (V)	12
Timing Range	0.1s - 180hrs

### PHYSICAL ATTRIBUTES

Operational Temperature Range (°C)	-10 to +50
Storage Temperature (°C)	-30 - +70

### PROTECTION & STANDARDS

Degree of Protection	IP40 (Timer), IP20 (Socket)
Pollution Degree	2
Standards and Approvals	EN 61812-1:2011, EN IEC 63000:2018

## RESOURCES

Product catalogue (Flipbook)

[Download from here](#)

---