

## Product No: 101150877

### SCHMERSAL RED & GREEN LED INDICATOR LAMP G24-M20

Note: Individual coding available on request



#### General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	Low
EAN	4030660000000
eCl@ss Number, Version 11.0	23-13-01-03
eCl@ss Number, Version 9.0	27-27-26-03
ETIM 6.0	EC000632
ETIM 7.0	EC001029
Housing Construction Form	Norm construction design
Product Type	Accessory
Working Principle	Electromechanical

#### Technical Attributes

No. of Auxiliary Contacts	1
Contact Material	Silver
Maximum Actuating Speed (m/s)	1
Maximum Cable Cross Section (mm <sup>2</sup> )	2 x 1.5
Maximum Fuse Rating	10 A gG D-fuse slow blow
Minimum Actuating Speed (mm/min)	1440
Minimum Cable Cross Section (mm <sup>2</sup> )	2 x 0.75
Minimum Mechanical Life	1000000 Operations
Minimum Positive Break Force (N)	15

No. of Safety Contacts	1
Overvoltage Category	3
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	500
Rated Short-circuit Current (A)	1000
Resistance to Shock (g/ms)	30 / 11
Switching Element	Opener (NC)
Switching Principle	Slow action
Terminal Type	Connector
Thermal Test Current (A)	0.25
Utilisation Category	DC-13   AC-15
Utilisation Category AC-15	1.5 A

#### Physical Attributes

Actuator Type	Angle roller lever
Enclosure Material	Aluminium
Gross Weight (g)	272.22
Maximum Ambient Temperature (°C)	70
Minimum Ambient Temperature (°C)	-15
Net Weight (g)	214.97
Storage Temperature (°C)	-25 to 85
Wire Cross-Section	0.25 mm

#### Dimensions

Sensor Height (mm)	25
Sensor Length (mm)	71.5

#### Protection & Standards

Degree of Protection	IP65
Standards	EN IEC 61496-1 / CLC/TS 61496-2

#### Resources



Product catalogue (Flipbook)

[Download from here](#)

---