

Product No: S802PVSP63

ABB S802PV-SP63 HIGH PERFORMANCE MCB S802PVSP63

FEATURES

- Maximum breaking capacity 5kA at 800V DC
- Rated impulse withstand voltage Uimp 8 Kv
- Cage terminals
- Standards IEC/EN 60947-2



General Information

Brand	ABB
Product Type	MCB

Technical Attributes

Breaking Capacity 800V DC - Icu (kA)	5
Current Limiting Class	3
Curve Type	B Curve
No. of Poles	2
No. of Protected Poles	2
Oversvoltage Category	3
Power Loss (W)	12.8
Rated Current (A)	63
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	1500
Rated Insulation Voltage DC (V)	1500
Rated Voltage (V)	400
Rated Voltage DC (V)	800
Release Type	B
Voltage Type	DC

Physical Attributes

Minimum Temperature (°C)	-25
Width in Number of Modular Spacings	3

Dimensions

Built-in Depth (mm)	82.5
Dimensions (mm)	54W x 95H x 82.5D

Protection & Standards

Degree of Protection	IP20
Pollution Degree	2

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------