

Product No: BXTML4BEC12

DEHN BXT COMBINED LIGHTNING CURRENT ARRESTER MODULE BXTML4BEC12

FEATURES

- Space-saving combined lightning current and surge arrester module
- With LifeCheck feature for protecting two pairs of balanced interfaces with diode protective circuit at the input, current loops (TTY) and optocoupler inputs
- LifeCheck detects thermal or electrical overload, indicates arrester has to be replaced
- This status is indicated contactlessly by the DEHNrecord LC / SCM / MCM reader



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	920362
Suitable For	Pluggable DIN Rail Mounted

Technical Attributes

Earth Fault Protection	DIN rail (top hat rail)
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	10
Maximum Continuous Voltage AC (V)	10.6
Maximum Continuous Voltage DC (V)	15
Nominal Discharge Current (8/20 μ s) - In (kA)	20
Nominal Load Current AC - I _n (A)	0.1
Nominal Voltage DC (V)	12
Voltage Protection Level - Up (kV)	19

Dimensions

Dimensions (mm)	12W x 45H x 51D
Weight (g)	24

Protection & Standards

Degree of Protection

IP20

Resources

Product catalogue (Flipbook)

[Download from here](#)