

Product No: DPICDEXD23024M

DEHN DPICDEXD23024M SPD T2 FOR SIGNALS AND MEASUREMENT EQUIP.

FEATURES

- - Dual surge protection for power supply & data interface
- - fault-proof Y circuit
- - Flameproof
- - Easy to mount on field devices
- - Standards IEC/EN 61643-21



General Information

Article No.	929969
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Lightning Impulse Current (10/350 μ s) - Iimp (kA)	1 (Line-PG)
Maximum Continuous Operating Voltage MCOV AC (V)	22.6
Maximum Continuous Operating Voltage MCOV DC (V)	32
Nominal Discharge Current (8/20 μ s) - In (kA)	0.15 (Line-Line)
Nominal Voltage (V)	24
Thread Size	M20 x 1.5 Male
Total Discharge Current (8/20 μ s) - Itotal (kA)	10
Voltage Protection Level - Up (kV)	≤ 0.058 (Line-Line)/ ≤ 0.9 (Line-PG)

Physical Attributes

Enclosure Material	Stainless steel (V4A)
--------------------	-----------------------

Protection & Standards

Degree of Protection	IP67
----------------------	------

Resources



Product catalogue (Flipbook)

[Download from here](#)
