

Product No: CSXi090V4C1

AuCom CSXi090V4C1 SOFT STARTER 90kW 170A 200-440VAC, CONTROL 110-240/380-440VAC

FEATURES

- - 18A ~ 200A Complete with Internal Bypass.
- - Mains voltage: 200~440VAC (V4).
- - Protection: IP20/IP00, 3 frames sizes.
- - Soft Start and Soft Stop Motor overload, Phase sequence. protection and Excess start time.
- - 7 Adjustments: Current ramp, Current limit, Motor trip class, Soft stop time, Excess start time, Auxiliary relay function, Phase sequence protection.
- - Compact and light weight.
- - Integrated bypass contactors.
- - Motor protection against operational overload, current spikes & fluctuations.
- - Plug-in communication interfaces.
- - Insulating finger guards.



General Information

Brand	AuCom
Product Type	Compact & Simple - CSXi

Technical Attributes

Motor Power - Medium Duty 400-415V (kW)	90
Rated Control Supply Voltage AC (V)	110- 240/380 - 440
Rated Current - Heavy Duty (A)	142
Rated Current - Medium Duty (A)	170
Rated Supply Voltage AC (V)	200 - 440

Physical Attributes

Operational Temperature Range (°C)	-10 to +60
------------------------------------	------------

Dimensions

Dimensions (mm)	202W x 240H x 214D
-----------------	--------------------

Protection & Standards

Degree of Protection

IP00

Resources

Product catalogue (Flipbook)

[Download from here](#)