

Product No: MSB304020G

IDE IDE66 ROLLED MILD STEEL SINGLE DOOR WALL MOUNTED ENCLOSURE 300Hx400Wx200Dmm GREY MSB304020G

FEATURES

- - Cold-rolled steel EN 10130+A1
- - Injected polyurethane sealing gasket
- - Primer coated and hardened RAL 7035 polyester paint, embossed, with UV protection
- - Substitute G with A for orange colour RAL 2008
- - Mounting plate included



General Information

| | |
|-----------------------|--|
| Brand | IDE |
| Customs Tariff Number | 85.38.10.00 |
| EAN | 8431044490267 |
| ETIM 8.0 | EC000261 |
| Product End of Life | It does not require specific recycling operations. |
| Product Type | Wall-mounting Cabinet |

Technical Attributes

| | |
|---------------------------------|--|
| Application | Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts. |
| Maximum Operational Voltage (V) | 1000 AC / 1500 DC |

Physical Attributes

| | |
|--------------------------------|--|
| Ambient Temperature Range (°C) | -25 to +60 |
| Cable Entry (mm) | 125H x 285W |
| Colour | RAL 7035 |
| Door Profiles | 2 |
| Door Type | Single |
| Finish | Coated with primer, and hardened polyester paint, textured, with UV protection |
| Installation | Surface |

| | |
|----------------------------------|--|
| Lock Type | 5-mm double-bit lock - One 1-point lock |
| Material | Cold-rolled steel EN 10130+A1 |
| Maximum Cabinet Load (kg) | 175 |
| Maximum Door Load (kg) | 25 |
| Maximum Mounting Plate Load (kg) | 150 |
| Mounting Plate | With flat mounting plate. 2-mm galvanised sheet steel |
| No. of Hinges | 2 |
| No. of Locks | 1 |
| Sealing Gasket | Injected polyurethane sealing gasket |
| Supply | Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied unassembled inside the packaging. |
| Type of Door | Single opaque door. Reversible |
| Wall Fixing (mm) | 260H x 260W |

Dimensions

| | |
|----------------------------|---|
| Dimensions (mm) | 300H x 400W x 200D |
| Mounting Plate Size (mm) | 270W x 350H |
| Thickness (mm) | Enclosure: 1.2 Door: 1.2 Cable entry lid: 2 |
| Usable Internal Space (mm) | 250H x 350W x 179D |
| Weight (kg) | 8.2 |

Protection & Standards

| | |
|---------------------------|------------------------|
| Certifications | UL508A |
| Degree of Protection | IP66 |
| Directive | 2014/35/EU |
| NEMA Degree of Protection | NEMA 1, 12, 4 |
| Rated Impact Resistance | IK08 |
| Standards | IEC 62208, IEC 61439-1 |
| Sustainability | RoHS - REACH |

Resources

Product catalogue (Flipbook)

[Download from here](#)
