

Product No: S801CC25

ABB S801CC25 HIGH PERF. MCB 25kA IP 25A 240VAC C CURVE

FEATURES

- - Protection against short circuit and thermal overload
- - Interchangeable terminal, failsafe cage or ring lug terminal
- - Laser printed data for quick identification
- - Contact position indication
- - Finger safety with IP20 terminals
- - Pole configuration 1P

General Information

Brand	ABB
Product Type	MCB
Series	S800C

Technical Attributes

Application	Commercial and Industrial
Breaking Capacity 230V AC - I _{cu} (kA)	25
Curve Type	C Curve
Maximum Operational Voltage AC (V)	254
Maximum Operational Voltage DC (V)	125
Minimum Operational Voltage AC (V)	12
No. of Poles	1P
Power Loss (W)	4.3/Pole
Rated Conditional Short-Circuit Current - I _{nc} (kA)	25
Rated Current (A)	25
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	500
Rated Operational Voltage AC (V)	230/400
Rated Operational Voltage DC (V)	125

Rated Voltage AC (V)	230
----------------------	-----

Physical Attributes

Housing Material	Insulation group I, RAL 7035
Mounting Type	DIN Rail

Dimensions

Cable Cross Section - Flexible (mm ²)	Top/Bottom - 70/70
Cable Cross Section - Solid/Stranded (mm ²)	Top/Bottom - 50/50
Dimensions (mm)	95H x 82.5D x 27W
Pole Width (mm)	27

Protection & Standards

Degree of Protection	IP20
Pollution Degree	3
Standards and Approvals	AS/NZS 60898-1, AS/NZS 60947-2, UL 1077

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------