

Product No: DRM2P75

DEHN 1PH CLASS3 4kA 8/20US IN-LINE 75VAC SURGE RAIL DRM2P75

FEATURES

- Two-pole DEHNrail modular surge arrester consisting of a base part and plug-in protection module
- High discharge capacity due to heavy-duty zinc oxide varistor / spark gap combination
- For protecting the power supply circuit of industrial electronics equipment against transient surges in switchgear cabinets
- For installation in conformity with the lightning protection zone concept at the boundaries from 1 " 2 and higher



General Information	
Brand	DEHN
Product Type	Surge Protection Device
Reference No.	953203
Suitable For	Power Supply Systems

Technical Attributes		
Maximum Continuous Voltage AC (V)	75	
Maximum Continuous Voltage DC (V)	75	
No. of Poles	2	
Nominal Discharge Current (8/20µs) - In (kA)	2	
Nominal Load Current AC - I⊠ (A)	25	
Nominal Voltage AC (V)	60	
Total Discharge Current (8/20µs) - Itotal (kA)	4	

Dimensions	
Dimensions (mm)	73W x 90H x 18D
Weight (g)	89.8
Weight (kg)	0.079



Protection & Standards	
Degree of Protection	IP20
Standards and Approvals	EN 61643-1

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>