

**Product:** GRM20-ZZZZTTTTTSZ9HHS

**Configurator:** GRM20-ZZZZTTTTTSZ9HHS



### Configurator Description

The GREYHOUND media modules can be ordered in versions from all-copper to all-fiber, depending on the individual need.

### Technical Specifications

#### Product description

Description	GREYHOUND Fast Ethernet Media Module
Part Number	942122202
Port type and quantity	8 x ports in total ; 2x FE SFP slot ; 2x FE SFP slot ; 2x FE/RJ45 ; 2x FE/RJ45

#### Network size - length of cable

Twisted pair (TP)	port 2 and 4: 0-100 m; port 6 and 8: 0-100 m;
Single mode fiber (SM) 9/125 µm	port 1 and 3: see SFP modules; port 5 and 7: see SFP modules;
Single mode fiber (LH) 9/125 µm (long haul transceiver)	port 1 and 3: see SFP modules; port 5 and 7: see SFP modules;
Multimode fiber (MM) 50/125 µm	port 1 and 3: see SFP modules; port 5 and 7: see SFP modules;
Multimode fiber (MM) 62.5/125 µm	port 1 and 3: see SFP modules; port 5 and 7: see SFP modules;

#### Power requirements

Operating Voltage	power supply via GREYHOUND switch
Power consumption	9 W
Power output in BTU (IT)/h	31

#### Ambient conditions

MTBF (Telecordia SR-332 Issue 3) @ 25°C	15 248 004 h
Operating temperature	0-+60 °C
Storage/transport temperature	-40-+70 °C
Relative humidity (non-condensing)	5-95 %

#### Mechanical construction

Weight	470 g
Protection class	IP30

#### Mechanical stability

IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks

#### EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	8 kV contact discharge, 15 kV air discharge
EN 61000-4-3 electromagnetic field	35 V/m (80-2700 MHz); 1 kHz, 80% AM
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line); data line: 1 kV; IEEE1613: power line 5kV (line/earth)
EN 61000-4-6 Conducted Immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EN 61000-4-16 mains frequency voltage	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s

## EMC emitted immunity

EN 55022	EN 55032 Class A
FCC CFR47 Part 15	FCC 47CFR Part 15, Class A

## Approvals

Basis Standard	CE, FCC, EN61131
Safety of industrial control equipment	EN60950

## Scope of delivery and accessories

Scope of delivery	Device, General safety instructions
-------------------	-------------------------------------

## Further Instructions

Product Documentation	<a href="https://www.doc.hirschmann.com/index.html">https://www.doc.hirschmann.com/index.html</a>
Certificates	<a href="https://www.doc.hirschmann.com/certificates.html">https://www.doc.hirschmann.com/certificates.html</a>

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.