

Product No: OS250D12BBP

ABB ABB SWITCH FUSE 250A 3P DIN HANDLE+SHAFT, FRONT OPERATED OS250D12BBP

FEATURES

- Pistol Handle
- Operating Mode: Front Operated
- IEC 60947-3
- Base mount



General Information

Brand	ABB
Product Type	Fuse Switch - DIN Type

Technical Attributes

Net Weight (kg)	3
No. of Poles	3P
Power Loss (W)	23
Rated Conditional Short-Circuit Current - Inc (kA)	80
Rated Current (A)	250 (Main Circuit)
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage (V)	1000
Rated Operational Current AC-21A 500V (A)	250
Rated Operational Current AC-22A 500V (A)	250
Rated Operational Current AC-22A 690V (A)	250
Rated Operational Power AC-23A 415V (kW)	145
Rated Operational Power AC-23A 500V (kW)	170
Rated Operational Power AC-23A 690V (kW)	250
Rated Operational Voltage AC (V)	690
Terminal Type	Lug terminals
Tightening Torque (Nm)	30 ... 44

Physical Attributes

Handle Type	Pistol Handle
Mounting Type	Base mounting

Dimensions

Dimensions (mm)	208W x 149H x 203D
Fuse Size	NH0, NHI

Protection & Standards

Pollution Degree	3
Standards	IEC 60947-3