

Product No: 942 274-001

HIRSHMANN SPIDER III STANDARD LINE, 5X 10/100/1000 BASE TX, RJ45 & 1X 100/1000BASE FX SFP, 12-24V DC; POE+ 942274001

FEATURES

- SPIDER III Standard Line Switches are affordable, entry-level switches for smaller infrastructures and field-level networks.
- SPIDER III Power over Ethernet Switches meet the needs of varied sectors and applications, especially automation environments that require reduced cabling.
- SPIDER III Premium Line Switches satisfy many industry-specific standards (like E1, DNV & ATEX) and are optimal for use in harsh environments, particularly with temperature.



General Information	
Brand	HIRSHMANN
Product Type	Unmanaged
Series	SPIDER-SL

Technical Attributes	
Current Consumption (mA)	0.27 at 24VDC
No. of 1GB Ports	6
No. of Ethernet Ports	5
No. of Fiber Ports	1
Nominal Power (W)	139.7
Port Quantity and Type	1 x GE FX, 4 x PoE+
Power Consumption (W)	140W with 120W PoE Output
Rated Maximum Operational Voltage DC (V)	57
Rated Minimum Operational Voltage DC (V)	12
Rated Operational Voltage DC (V)	12 - 57
Switch Type	Switch - Unmanaged



Physical Attributes	
Maximum Temperature (°C)	70
Minimum Temperature (°C)	-40
Mounting Type	DIN Rail / Wall
Operational Temperature Range (°C)	-40 to +70

Dimensions	
Dimensions (mm)	130H x 35W x 121D

Protection & Standards	
Degree of Protection	IP30
Standards and Approvals	cUL 61010-1/61010-2-201

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>