

## Product No: 1SDA067871R1

ABB XT2H 160 EKIP LSI IN=160A 3P F F 1SDA067871R1

### FEATURES

- Fixed Three Pole
- Front Terminals
- Solid-state release
- ABB EcoSolutions



### General Information

Brand	ABB
Product Type	MCCB
Version	Fixed

### Technical Attributes

Design of Control Element	Toggle
Breaking Capacity 415V AC - Icu (kA)	70
I - Short-circuit Current Setting I3 (A)	160 - 1600
L - Overload Current Setting II (A)	64 - 160
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Front Side
No. of Poles	3
Power Loss (W)	10.8
Rated Current (A)	160
Rated Frequency (Hz)	50/60
Rated Instantaneous Short-Circuit Current - Ii (A)	160
Rated Insulation Voltage (V)	1000
Rated Uninterrupted Current - Iu (A)	160
Rated Voltage (V)	690
S - Selective Short-circuit Current Setting I2 (A)	160 - 1600
Trip Unit	EKIP DIP LSI

### Dimensions

Dimensions (mm)	90W x 130H x 82.5D
-----------------	--------------------

## Protection & Standards

Degree of Protection	IP20
Standards and Approvals	IEC 60947-2