

Product No: 101060279

SCHMERSAL AZ 13 KU POSITIVE-OPERATION DOOR CONTACT 101060279



General Information

Brand	SCHMERSAL
-------	-----------

Technical Attributes

Actuating Force (N)	1.6
Actuating Stroke (mm)	7
Contact Material	Silver-plated Cu Rivets
Maximum Fuse Rating	6 A gG D-fuse
Minimum Mechanical Life	1000000 Operations
Minimum Positive Break Force (N)	10
No. of Safety Contacts	1
Rated Insulation Voltage (V)	500
Rated Operational Current AC-15 (A)	2
Rated Operational Current DC-13 (A)	2
Rated Operational Voltage AC-15 (V)	230V AC
Rated Operational Voltage DC-13 (V)	200V DC
Switching Element	Opener (NC)
Switching Principle	Self-cleaning Pressure Contact
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	4
Utilisation Category	DC-13

Physical Attributes

Cable Entry	Single Conductor Version with Connecting Funnel
Housing Material	Plastic, Glass-fibre Reinforced Thermoplastic, Self-extinguishing
Maximum Ambient Temperature (°C)	70
Minimum Ambient Temperature (°C)	-30

Dimensions

Depth (mm)	19
Height (mm)	55
Width (mm)	44

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	EN 81-20

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------