

## Product No: HS5L-XH7Y4M-G

### IDEC INTERLOCK 2 CONTACTS SOLENOID LOCK SAFETY\_SWITCH HS5L-XH7Y4M-G

#### FEATURES

- 1400N Locking Strength
- Gold-plated contacts suitable for small loads
- The head orientation can be rotated
- allowing 8 different actuator entries
- Applicable Standards: EN ISO14119
- GS-ET-19 (TUV approval)
- EN60947-5-1 (TUV approval)
- UL508 (UL Listing)
- CSA C22.2 No. 14 (c-UL listed)
- IEC 60204-1/EN60204-1



#### General Information

|              |                         |
|--------------|-------------------------|
| Brand        | IDEC                    |
| Product Type | Safety Interlock Switch |

#### Technical Attributes

|                                 |         |
|---------------------------------|---------|
| Contacts                        | 2       |
| Minimum Electrical Life         | 100000  |
| Minimum Mechanical Life         | 2000000 |
| Rated Insulation Voltage (V)    | 250     |
| Rated Thermal Current - Ith (A) | 2.5     |

#### Physical Attributes

|                                    |           |
|------------------------------------|-----------|
| Operational Temperature Range (°C) | -25 to 55 |
|------------------------------------|-----------|

#### Dimensions

|                 |                  |
|-----------------|------------------|
| Dimensions (mm) | 35W x 40H x 127D |
| Weight (g)      | 300              |

#### Protection & Standards

|                      |      |
|----------------------|------|
| Degree of Protection | IP67 |
|----------------------|------|

Pollution Degree

3

## Resources

Product catalogue (Flipbook)

[Download from here](#)