

Product No: CAF611K

ABB FRONT MOUNTED INST AUX CONTACT 1NO 1NC TO SUIT K6 KC6 CAF611K



General Information

Brand	ABB
Product Type	Accessory
Suitable For	K6, KC6

Technical Attributes

Cable Sections - Auxiliary Circuit	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Conventional Free-Air Thermal Current - I _{th} (A)	Auxiliary Circuit 6 A
No. of Auxiliary Contacts	1 NO + 1 NC
No. of Poles	2
Rated Frequency (Hz)	50 / 60
Rated Impulse Withstand Voltage (kV)	Auxiliary Circuit 6 kV
Rated Insulation Voltage	690 V
Rated Operational Voltage AC (V)	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Tightening Torque (Nm)	Auxiliary Circuit 0.8 ... 1.1 N·m
Wire Stripping Length (mm)	9

Physical Attributes

Ambient Temperature (°C)	Operation -25 ... +55 °C Storage -40 ... +80 °C
--------------------------	---

Dimensions

Dimensions (mm)

29 * 47.5 * 26.5 [H*W*D]

Protection & Standards

Standards

IEC/EN 60947-1, IEC/EN 60947-4-1, IEC/EN 60947-5-1, UL 60947-1, UL 60947-4-1
