

Product No: MCRA031AT1

ABB MCRA031AT1 MINI CONTACTOR RELAY 3NO+1NC 24V 50/ 60HZ MCRA031AT1

FEATURES

- Compact design, ideal for installations with limited space
- Four poles for versatile and efficient electrical switching
- Secure and convenient electrical connections
- Options for wall or rail mounting to accommodate different installations needs



General Information	
Brand	ABB
Product Type	Mini Contactor Relay
Series	М

Technical Attributes	
Actuating Voltage Type	AC
Auxiliary Contacts	3NO/INC
Connection Type	Screw Connection for Auxiliary Circuit
Mode of Operation	AC
No. of Normally-closed Auxiliary Contacts	1
No. of Normally-open Auxiliary Contacts	3
No. of Poles	4
Operating Voltage AC (V)	690
Operating Voltage DC (V)	440
Operating Voltage Type	AC
Power Loss (W)	0.4/pole
Rated Control Circuit Voltage AC (V)	24
Rated Control Supply Voltage AC (V)	24
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	750
Rated Operational Current (A)	6



Technical Attributes	
Rated Operational Current AC-15 240V (A)	6
Rated Operational Current AC-15 400V (A)	4
Rated Operational Voltage AC (V)	690
Rated Supply Voltage AC (V)	24
Short-Circuit Protective Device	10A, fuse type gG
Terminal Type	Screw

Physical Attributes	
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-40 to +55

Dimensions	
Dimensions (mm)	45W x 48H x 56D

Protection & Standards	
Degree of Protection	IP20

Resources

Product catalogue (Flipbook)

Download from here