

Product No: 943 940-999-011

**HIRSCHMANN MANAGED RACKMOUNT SWITCH MAR1020-99
JJJJJJJJJJTTTTTTTTTTTTTT99SMMHPH 943 940-999-011**

FEATURES

- Ruggedized Managed Rackmount Switch
- 2 Combo Ports: 2 x 10/100/1000Base-TX or 2 x Gigabit Ethernet SFP
- Operating Temperature Range: -40 °C to +85 °C
- Dual Power Supply Input: Supports 24V, 36V, and 48V DC (plug-in connector)
- Layer 2 Professional Network Management Features
- Approvals Include cUL508, cUL1604 Class I Division II, Germanischer Lloyd Certification
- IP30 Protection Rating

General Information

Brand	HIRSCHMANN
Series	MAR1030

Technical Attributes

No. of 100Mb Ports	22
No. of Ethernet Ports	12
No. of Fiber Ports	10
Rated Maximum Operational Voltage AC (V)	230
Rated Maximum Operational Voltage DC (V)	250
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110

Physical Attributes

Maximum Temperature (°C)	60
Minimum Temperature (°C)	0
Mounting Type	19" Control Cabinet

Protection & Standards

Degree of Protection	IP30
Standards and Approvals	IEC 61850-3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------