

## Product No: OKA20S3RF2

### ABB OKA20S3RF2 F200 EMC ENCLOSED SWITCH OKA20S3RF2

#### FEATURES

- 3 pole, F200 EMC enclosed switch disconnecter
- Mounted auxiliary contact: 1NO, 0NC
- Aluminium Enclosure
- Red round handle available
- Interlocked cover
- Handle is padlockable in ON and OFF position with max. 3 padlocks
- Applications: rise buildings, car parks, tunnels or any place where there are exhaust fans that should stay on during fire
- Degree of protection: IP65



#### General Information

Brand	ABB
Product Type	Enclosed
Suitable For	Distribution Board Installation
Type	Main Switch

#### Technical Attributes

Conventional Thermal Current - I <sub>the</sub> (A)	32
Main Circuit Electrical Connection	Screw Connection
Maximum Operational Voltage AC (V)	750
No. of Normally-open Auxiliary Contacts	1
No. of Poles	3
Rated Operational Current AC-22A 415V (A)	20
Rated Operational Current AC-23A 380-415V (A)	20
Rated Operational Current AC-23A 415V (A)	20
Rated Operational Current AC-23A 500V (A)	20
Rated Operational Power AC-23A 380-415V (kW)	11
Rated Operational Voltage (V)	750
Rated Short-Time Withstand Current - I <sub>cw</sub> (kA)	0.5
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	0.5
Rated Uninterrupted Current - I <sub>u</sub> (A)	32

### Physical Attributes

Cable Outlets per Side	2xM25+M20/2xM25+M20
Control Element Colour	Red
Enclosure Material	Aluminium
Handle Colour	Red
Handle Type	Round

### Dimensions

Dimensions (mm)	130W x 165H x 103D
Weight (kg)	1.25

### Protection & Standards

Degree of Protection	IP65
NEMA Degree of Protection	1