

Product No: HP10M5

MERSEN FUSE LINK 5A 1000V DC gPV 10X38mm FERRULE TYPE HP10M5

FEATURES

- Low fault current Interruption
- Durable construction for long-term performance
- Temperature cycle withstand capability
- Breaking capacity 50kA
- Standard ferrule terminal



General Information

| | |
|---------------|-----------|
| Brand | MERSEN |
| Pack Quantity | 10 |
| Product Type | Fuse Link |

Technical Attributes

| | |
|--------------------------|---------|
| Interrupting Rating (kA) | 50 |
| Maximum Fuse Rating (A) | 6.75 |
| Power Loss (W) | 1.12 |
| Rated Current (A) | 5 |
| Rated Voltage DC (V) | 1000 |
| Suitable Fuse Holder | CUS101 |
| Terminal Type | Ferrule |
| Utilization Category | gPV |

Physical Attributes

| | |
|-------------------|-------------------|
| Terminal Material | Tin-Plated Copper |
|-------------------|-------------------|

Dimensions

| | |
|---------------|----|
| Diameter (mm) | 10 |
| Length (mm) | 38 |

Protection & Standards

Standards and Approvals

IEC 60269-6 Approved (CB Tested)

Resources

Product catalogue (Flipbook)

[Download from here](#)
