

Product No: TF42-20

ABB TF42-20 THERMAL OVERLOAD RELAY 16 ... 20 A TF42-20

FEATURES

- Economic electromechanical protection device for the main circuit
- Reliable and fast protection for motors in the event of overload or phase failure
- Trip class 10 device
- Temperature compensation
- Automatic or manual reset selectable
- STOP function and a trip indication



General Information	
Brand	ABB
Product Type	Thermal Overload Relay
Suitable For	AF09 - AF38

Technical Attributes	
Auxiliary Contacts	INO/INC
Current Setting Range (A)	16
Main Circuit Electrical Connection	Screw Connection
Maximum Operational Voltage AC (V)	690
No. of Auxiliary Change-over Contacts	1
No. of Normally-closed Auxiliary Contacts	1
No. of Normally-open Auxiliary Contacts	1
No. of Poles	3
Power Loss (W)	1.8/pole
Rated Frequency (Hz)	50/60
Rated Frequency (Hz) Rated Impulse Withstand Voltage (kV)	50/60 6
Rated Impulse Withstand Voltage (kV)	6
Rated Impulse Withstand Voltage (kV) Rated Insulation Voltage (V)	6
Rated Impulse Withstand Voltage (kV) Rated Insulation Voltage (V) Rated Operational Voltage AC (V)	6 690 690



Thermal Current Setting Range (A)	16 - 20
Trip Class	10

Physical Attributes	
Mounting Type	Direct Attachment

Dimensions	
Dimensions (mm)	45W x 88.3H x 70.5D

Protection & Standards	
Degree of Protection	IP10 (Main Terminals), IP20 (Housing)
Pollution Degree	3

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>