

ABB E22N3ETG25W ACB E2.2N 3P 66KA WITHDRAWABLE 2500A EKIP TOUCH LSIG

E22N3ETG25W



GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I _{cu} (kA)	66
G (0.1 to 1 x I _n) - I ₄ (A)	250-2500
I (1.5 to 15 x I _n) - I ₃ (A)	3750-37500
L (0.4 to 1 x I _n) - I ₁ (A)	1000-2500
No. of Poles	3P
Power Loss (W)	550
Rated Current (A)	2500
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I _{cw} (kA/1s)	66
Rated Uninterrupted Current - I _u (A)	2500
S (0.6 to 10 x I _n) - I ₂ (A)	1500-25000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG

DIMENSIONS

Frame Size	E2.2
------------	------

PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
